

NYLON SOCKET CAP SCREWS (CONTINUED)



Part Number: A12 + Code

CODE	THREAD	LENGTH
116	4-40	1-3/8
117	4-40	1-1/2
118	6-32	7/8
119	6-40	1/4
120	6-40	3/8
121	6-40	3/4
122	6-40	1
123	10-24	3/16

CODE	THREAD	LENGTH
124	10-24	1/4
125	10-24	5/16
126	10-24	3/8
127	10-24	1/2
128	10-24	5/8
129	10-24	3/4
130	10-24	1
131	10-24	1-1/4

CODE	THREAD	LENGTH
132	10-24	1-1/2
133	10-32	1/8
134	10-32	2
135	1/4-20	2-1/2
136	1/4-28	3/16
137	1/4-28	3/8
138	1/4-28	3/4
139	1/4-28	1

KNURLED HEAD THUMB SCREWS



Part Number: E14 + Code

CODE	THREAD	LENGTH
001	4-40	3/16
002	4-40	1/4
003	4-40	3/8
004	4-40	1/2
005	4-40	3/4
006	6-32	1/4
007	6-32	3/8
008	6-32	1/2
009	6-32	3/4
010	6-32	1
011	8-32	3/16
012	8-32	3/8
013	8-32	1/2
014	8-32	3/4
015	8-32	1
016	10-24	1/2
017	10-24	3/4
018	10-24	1
019	10-24	1-1/4
020	10-24	2
021	10-32	3/8
022	10-32	1/2

CODE	THREAD	LENGTH
023	10-32	3/4
024	10-32	1
025	10-32	1-1/16
026	10-32	1-1/2
027	10-32	2
028	1/4-20	1/2
029	1/4-20	3/4
030	1/4-20	1
031	1/4-20	1-1/4
032	1/4-20	1-1/2
033	5/16-18	1/2
034	5/16-18	1
035	5/16-18	1-1/2
036	5/16-18	2
037	3/8-16	1/2
038	3/8-16	1
039	3/8-16	1-1/2
040	3/8-16	2
041	1/2-13	1/2
042	1/2-13	1
043	1/2-13	1-1/2
044	1/2-13	2

PLASTIC THUMB SCREWS




Part Numbers: NYLON: E30 + Code
DELRIN: E31 + Code

CODE	THREAD SIZE	LENGTH	HEAD DIAMETER 3/16 THICK	SHOULDER UNDER HEAD 1/4 DIA.-1/8 LONG
001	8-32	1/4	3/8	NO
002	8-32	5/16	3/8	NO
003	8-32	3/8	3/8	NO
004	8-32	3/8	1/2	NO
005	8-32	1/2	1/2	NO
006	8-32	9/16	3/8	YES
008	10-32	3/8	1/2	NO

- Thick-headed, deep-fluted for positive finger grip
- Optional, under head washer-like bases
- The advantages of Nylon, Delrin for locking, adjusting, clamping applications

ECONOMY GRADE NYLON THUMB SCREWS



Part Numbers: Unslotted: E11 + Code
Slotted: E12 + Code

CODE	THREAD	LENGTH
001	4-40	1/4
002	4-40	3/8
003	4-40	1/2
004	4-40	5/8
005	4-40	3/4
006	6-32	1/4
007	6-32	3/8
008	6-32	1/2
009	6-32	5/8
010	6-32	3/4
011	6-32	1
012	8-32	3/8
013	8-32	1/2
014	8-32	3/4

CODE	THREAD	LENGTH
015	8-32	1
016	8-32	1-1/4
017	10-32	3/8
018	10-32	1/2
019	10-32	3/4
020	10-32	1
021	10-32	1-1/4
022	10-32	1-1/2
023	1/4-20	1/2
024	1/4-20	3/4
025	1/4-20	1
026	1/4-20	1-1/4
027	1/4-20	1-1/2

- Allows frequent application adjustments
- Thick, knurled heads for secure hand grip
- Slotted and unslotted
- Tolerances ± .010