


NYLON ROUND THREADED STAND-OFFS/TAPPED SPACERS



Part Number: C33 + Code

CODE	THREAD	LENGTH	OD
001	4-40	1/4	1/4
002	4-40	3/8	1/4
003	4-40	1/2	1/4
004	4-40	3/4	1/4
005	4-40	1	1/4
006	6-32	1/4	1/4
007	6-32	3/8	1/4
008	6-32	1/2	1/4
009	6-32	3/4	1/4
010	6-32	1	1/4
011	8-32	1/4	1/4
012	8-32	3/8	1/4
013	8-32	1/2	1/4
014	8-32	3/4	1/4
015	8-32	1	1/4
016	8-32	1/4	5/16
017	8-32	3/8	5/16
018	8-32	1/2	5/16

CODE	THREAD	LENGTH	OD
019	8-32	3/4	5/16
020	8-32	1	5/16
021	10-32	1/4	3/8
022	10-32	3/8	3/8
023	10-32	1/2	3/8
024	10-32	3/4	3/8
025	10-32	1	3/8
026	10-32	1/4	1/2
027	10-32	3/8	1/2
028	10-32	1/2	1/2
029	10-32	3/4	1/2
030	10-32	1	1/2
031	1/4-20	1/4	1/2
032	1/4-20	3/8	1/2
033	1/4-20	1/2	1/2
034	1/4-20	3/4	1/2
035	1/4-20	1	1/2

- Tolerances: OD \pm .010, Length \pm .010
- On 3/4" & longer tap is 3/8" from each end and not continuous throughout

PHENOLIC ROUND THREADED STAND-OFFS




Part Number: C34 + Code

CODE	THREAD	LENGTH	OD
001	4-40	1/4	1/4
002	4-40	3/8	1/4
003	4-40	1/2	1/4
004	4-40	3/4	1/4
005	4-40	1	1/4
006	6-32	1/4	1/4
007	6-32	3/8	1/4
008	6-32	1/2	1/4
009	6-32	3/4	1/4
010	6-32	1	1/4

CODE	THREAD	LENGTH	OD
011	8-32	1/4	1/4
012	8-32	3/8	1/4
013	8-32	1/2	1/4
014	8-32	3/4	1/4
015	8-32	1	1/4
016	10-32	1/4	5/16
017	10-32	3/8	5/16
018	10-32	1/2	5/16
019	10-32	3/4	5/16
020	10-32	1	5/16

- Wide range of electrical and mechanical uses: raising chassis, subpanels, transformers
- High dielectric strength for creepless, heavy load use
- Dimensional stability over wide temperature use
- Resists abrasion, wear, moisture and high temperature deterioration

CPVC "SELF THREADING" HEX STAND-OFFS



Part Number: C35 + Code

CODE	SCREW SIZE	LENGTH	ID	HEX SIZE
001	4	3/8	.093	3/16
002	4	1/2	.093	3/16
003	4	5/8	.093	3/16
004	4	3/4	.093	3/16
005	4	7/8	.093	3/16
006	4	1	.093	3/16
007	6	1/2	.110	1/4
008	6	5/8	.110	1/4

CODE	SCREW SIZE	LENGTH	ID	HEX SIZE
009	6	3/4	.110	1/4
010	6	7/8	.110	1/4
011	6	1	.110	1/4
012	8	5/8	.141	3/8
013	8	3/4	.141	3/8
014	8	7/8	.141	3/8
015	8	1	.141	3/8

- Easy to apply, low in cost
- "Self-threading" allows assembly with any metal self-tapping screw