

METRIC HEX NUTS

Part Number: K70 + Code

CODE	THREAD SIZE	A/F	THK
001	M2 X 0.4	3.9	1.2
002	M2.5 X 0.45	4.9	1.8
003	M3 X 0.5	5.4	2.2
004	M3.5 X 0.5	6.9	2.7
005	M4 X 0.7	6.9	3.0

CODE	THREAD SIZE	A/F	THK
006	M5 X 0.8	7.9	4.3
007	M6 X 1.0	9.9	5.4
008	M8 X 1.25	12.9	6.4
009	M10 X 1.50	14.8	9.8
010	M12 X 1.75	17.74	10.54

METRIC WASHERS

Part Number: K71 + Code

CODE	SCREW SIZE	OD	ID	THK
001	M3	8.00	3.20	0.80
002	M4	9.00	4.30	0.80
003	M5	11.0	5.30	1.00

CODE	SCREW SIZE	OD	ID	THK
004	M6	12.00	6.40	1.50
005	M8	18.00	8.40	2.00
006	M10	22.00	10.50	2.50

NYLON THREADED STUDS



Part Number: D14 + Code

CODE	THREAD	LENGTH
001	10-32	3/4
002	10-32	1
003	10-32	1-1/2
004	10-32	2
005	10-32	2-1/2
006	1/4-20	3/4
007	1/4-20	1
008	1/4-20	1-1/2
009	1/4-20	2
010	1/4-20	2-1/2

CODE	THREAD	LENGTH
011	1/4-20	3
012	5/16-18	1
013	5/16-18	1-1/2
014	5/16-18	2
015	5/16-18	2-1/2
016	5/16-18	3
017	3/8-16	1
018	3/8-16	1-1/2
019	3/8-16	2

CODE	THREAD	LENGTH
020	3/8-16	2-1/2
021	3/8-16	3
022	3/8-16	4
023	1/2-13	1-1/2
024	1/2-13	2
025	1/2-13	2-1/2
026	1/2-13	3
027	1/2-13	4
028	1/2-13	5

- Injection molded threaded studs with chamfer on both ends are available in several of the most popular sizes and lengths.
- Threaded studs are molded in natural Nylon 6/6 UL 94V2. These studs are resistant to most chemicals, electrically insulating, non-magnetic, lightweight, low thermal conductivity, vibration and abrasion resistant.