

NYLON ROLLED "LOC-SEAL" WASHERS




Part Number: C58 + Code

CODE	SCREW SIZE	ID	WALL
002	2	.088	.012
003	3	.101	.012
004	4	.116	.013
006	6	.142	.015
007	8	.168	.015
008	10	.194	.015
009	1/4	.252	.019

CODE	SCREW SIZE	ID	WALL
010	5/16	.316	.020
011	3/8	.379	.022
012	7/16	.441	.022
013	1/2	.504	.022
014	5/8	.630	.025
015	3/4	.755	.028

- Patented rolled head design insulates screw head, fills thread; seals and locks into place
- Can be used under screw head and/or nut
- Recommended maximum continuous temperature: 250°F

NYLON ROLLED "LOC-SEAL" SCREW INSULATORS



Part Number: C28 + Code

CODE	SCREW SIZE	LENGTH	ID	WALL
001	1	1/4	.075	.012
002	2	1/4	.088	.012
003	3	1/4	.101	.012
004	3	1/2	.101	.012
005	4	1/4	.116	.013
006	4	1/2	.116	.013
007	4	3/4	.116	.013
008	5	1/4	.129	.014
009	5	1/2	.129	.014
010	5	3/4	.129	.014
011	6	1/4	.142	.015
012	6	1/2	.142	.015
013	6	3/4	.142	.015
014	8	1/4	.168	.015

CODE	SCREW SIZE	LENGTH	ID	WALL
015	8	1/2	.168	.015
016	8	3/4	.168	.015
017	10	1/4	.194	.017
018	10	1/2	.194	.017
019	10	3/4	.194	.017
020	1/4	1/4	.252	.019
021	1/4	1/2	.252	.019
022	1/4	3/4	.252	.019
023	5/16	1/4	.316	.020
024	5/16	1/2	.316	.020
025	5/16	3/4	.316	.020
026	3/8	1/4	.379	.022
027	3/8	1/2	.379	.022
028	3/8	3/4	.379	.022

- Same patented rolled head design as washers, with varying sleeve extensions
- Tightening of assembly allows cold flow of plastic into double flanged grommet
- Can be used with nylon flat washer, without hole protusion
- Use with metal rivets allows permanent fastener insulation
- Spinning or heat forming sleeve end allows use as eyelets or grommets