

## TEFLON® (TFE) MACHINED SCREWS

Please refer to illustrations of head styles on page 8

**Part Numbers: Hex Head: S47 + Code**

**Round Head: S48 + Code**

**Fillister Head: S49 + Code**

**Flat Head: S50 + Code**

**Pan Head: S51 + Code**

CODE	THREAD	LENGTH
001	2-56	1/8
002	2-56	1/4
003	4-40	1/4
004	4-40	3/8
005	4-40	1/2
006	4-40	5/8
007	4-40	3/4
008	4-40	1
009	6-32	1/4
010	6-32	3/8

CODE	THREAD	LENGTH
011	6-32	1/2
012	6-32	5/8
013	6-32	3/4
014	6-32	1
015	8-32	1/4
016	8-32	3/8
017	8-32	1/2
018	8-32	5/8
019	8-32	3/4
020	8-32	1

CODE	THREAD	LENGTH
021	10-32	3/8
022	10-32	1/2
023	10-32	5/8
024	10-32	3/4
025	10-32	1
026	1/4-20	3/8
027	1/4-20	1/2
028	1/4-20	5/8
029	1/4-20	3/4
030	1/4-20	1

- Choice for extreme environmental conditions
- Highest heat resistance to 500°F
- Resistant to all organic solvents
- Moisture absorption is zero
- Electrical properties are outstanding
- Tensile shear and torque strength are low
- Extremely low friction co-efficient

## TEFLON® HEX CAP SCREWS

**Part Number: A23 + Code**

CODE	THREAD	LENGTH
001	1/4-20	1/2
002	1/4-20	3/4
003	1/4-20	1
004	1/4-20	1-1/2
005	1/4-20	2
006	5/16-18	1/2
007	5/16-18	3/4
008	5/16-18	1
009	5/16-18	1-1/2
010	5/16-18	2

CODE	THREAD	LENGTH
011	3/8-16	3/4
012	3/8-16	1
013	3/8-16	1-1/2
014	3/8-16	2
015	3/8-16	2-1/2
016	1/2-13	1
017	1/2-13	1-1/2
018	1/2-13	2
019	1/2-13	2-1/2
020	1/2-13	3

- Unslotted