


## NYLON WASHERS



### Part Number: C18 + Code

CODE	SCREW SIZE	ID	OD	THICK
001	2	.090	.250	.032
002	2	.090	.250	.062
003	2	.090	.250	.093
004	2	.090	.250	.125
005	4	.115	.250	.032
006	4	.115	.250	.062
007	4	.115	.250	.093
008	4	.115	.250	.125
009	4	.115	.281	.047
010	4	.125	.250	.062
011	4	.125	.312	.062
012	4	.125	.375	.062
013	4	.125	.437	.062
014	6	.140	.312	.032
015	6	.140	.312	.047
016	6	.140	.312	.062
017	6	.140	.312	.093
018	6	.140	.312	.125
019	6	.147	.250	.062
020	6	.147	.375	.062
021	6	.147	.437	.062
022	8	.171	.375	.032
023	8	.171	.375	.062
024	8	.171	.375	.093
025	8	.171	.375	.125
026	8	.174	.250	.062
027	8	.174	.312	.062
028	8	.174	.437	.062
029	8	.174	.500	.062
030	10	.194	.375	.032
031	10	.194	.375	.062
032	10	.194	.375	.093
033	10	.194	.375	.125
035	10	.200	.437	.062
036	10	.200	.500	.062

CODE	SCREW SIZE	ID	OD	THICK
037	10	.203	.562	.062
038	10	.200	.625	.062
040	1/4	.257	.500	.032
041	1/4	.257	.500	.062
042	1/4	.257	.500	.093
043	1/4	.257	.500	.125
044	1/4	.260	.562	.062
045	1/4	.250	.625	.062
046	1/4	.260	.625	.125
047	1/4	.260	.687	.062
048	1/4	.260	.687	.125
049	1/4	.260	.750	.062
050	1/4	.260	.745	.125
051	5/16	.317	.500	.032
052	5/16	.317	.500	.062
053	5/16	.317	.500	.093
054	5/16	.317	.500	.125
055	3/8	.380	.531	.093
056	3/8	.380	.625	.032
057	3/8	.380	.625	.062
058	3/8	.380	.625	.093
059	3/8	.380	.625	.125
060	3/8	.390	.500	.062
062	3/8	.390	.687	.062
063	3/8	.390	.687	.125
064	3/8	.390	.750	.062
065	3/8	.394	.757	.125
066	7/16	.443	.750	.032
067	7/16	.443	.750	.062
068	7/16	.443	.750	.093
069	7/16	.443	.750	.125
070	1/2	.505	.750	.032
071	1/2	.505	.750	.062
072	1/2	.505	.750	.093
073	1/2	.505	.750	.125

- Elastic and resilient, allows conformity to irregular surfaces
- Seals, dampens vibration
- Versatile; insulation, shock load use
- Low/no lubrication requirement allows anti-friction bearing
- Can be used as spacer